

DRIVE MOTOR C/W
INVERTER CONTROL

ELECTRICAL JUNCTION BOX

PUMP LIFTING EYE
BOTH SIDES

PUMP CLEANING PORT
BOTH SIDES

EMS Mechanical Ram Pumps model CVRD300 double Twin Ram Pump has seldom got any wearing on the ram body due to the hardness of the ram body, the maintenance downtime is very minimal during the operating lifetime. The latest design of Ram Seal by special Packing allows even long wearing lifetime.

Capable to provide a self lift of solids stated with a suction lift of 8m from sludge holder, digestion tank.

RAM PUMP DATA

MODEL: CVRD300
MAX PUMP PRESSURE: 2 - 6bar
MAX PUMP OUTPUT: 900lpm
DRIVE MOTOR: 7.5 - 18.5kW
POWER SUPPLY: 415v-3ph-50Hz
MOTOR HEATER: 1ph-50Hz
PUMP WEIGHT (STATIC): 2550kg
PUMP WEIGHT (DYNAMIC): 2700kg

DRIVE MOTOR IS FITTED WITH AN INTEGRAL INVERTER CONTROL UNIT WITH ALL PARAMETERS FACTORY SET AT EMS Ltd. TO GIVE REQUIRED PUMP DUTY.
THE INVERTER CONTROL PROVIDES:a) OPTIMUM ENERGY EFFICIENCY
b) SOFT START & STOP
c) SYSTEM MONITORING WHICH PROVIDES

C) SYSTEM MONITORING WHICH PROVIL PROTECTION FOR CIT DELIVERY OVER PRESSURE

c1) DELIVERY OVER PRESSURE c2) BLOCKED SUCTION



